

MINECORP LIGHT ATTACK FIRE APPLIANCE FIT FOR PURPOSE





PB-0326-A

FEATURE OVERVIEW

4200 KG GVM SUSPENSION UPGRADE

FIRE CURTAINS FITTED TO ALL CAB WINDOWS

REVERSE ALARM

CONNECTION FOR EXTERNAL BATTERY CHARGING

POWERFUL DAVEY 5290HE HONDA GX270 PUMP

MANUAL HAND DIAPHRAGM PRIMER
PUMP

PUMP CONTROL PANEL AT THE REAR OF THE VEHICLE

CLASS A DOSATRON LIQUID FOAM PROPORTIONER

50 METRE HOSE REEL WITH 12V ELECTRIC REWIND

DURABLE & BAFFLED 550 LITRE ALLOY WATER TANK

SUCTION HOSE LOCKER

FOLD DOWN LOCKING STEPS

STAND PIPE STORAGE

DRIP TORCH STORAGE BRACKET

UNDERBODY TOOLBOX TO STORE DRIP TORCH & PUMP FUEL

NON SLIP SLIDE OUT STEP SYSTEM AT THE REAR

COMPLETE UNDERTRAY LIGHTING SYSTEM

LHS & RHS LOCKERS FOR SUPERIOR STORAGE CAPACITY

FRIDGE SLIDE

SLIDE OUT WORK BENCH

INCIDENT COMMANDERS STATION

EMERGENCY LIGHT BAR







Based on a Toyota LandCruiser 79 Series, this Light Attack Fire Appliance is ready to face extreme and demanding conditions.

Features

- Ingenious water tank design;
 Lowers the centre of gravity of the vehicle
 enhancing stability on steep slopes
 Allowing the full 550 litres of fire-fighting
 water to be used even while the appliance is
 standing on up to a 20-degree angle, on any
 plane
- Sophisticated plumbing system;
 38mm delivery with Storz and blanking cap
 50mm return to the tank line for pump
 cooling purposes and enables tank refilling
 from suction hose
 50mm hard suction plumbed direct to pump
 inlet side with Storz fitting and blanking cap
 Pump Control Panel (includes pressure
 gauge, ignition switch, throttle controls and
 electronic water level indicator)
 Backflow prevention to hydrants/water main
- Siren, Emergency Lightbar, vehicle body, under-body and locker lighting control system - all operated from either inside the cab or from the rear Pump Control Panel
- Interlocked scene lights
- Storage Lockers;

Manufactured from aluminium Gas strut assisted and lockable LED strip lighting throughout for night time operations

Versatile drawers in both lockers
Adjustable shelves in both lockers
Shelves are lined with fuel and chemical
resistant rubber matting, preventing
equipment from moving around
Provisions for a fridge that can be mounted
on a slide
Slide out work bench with a load rating of

40KG

 Warning lights and buzzers to alert when running low on water, driving with locker doors open or ladders and steps deployed